

X1

35 to 47 Engine HP

McCORMICK



Tractor Model	X1.35	X1.45	X1.45C
Rated Engine HP	35	47	47
Rated Engine Speed	2800 RPM		
Rated PTO HP	29	42	42
Engine Type	3-cylinder diesel	4-cylinder diesel	
Displacement	1.7 L	2.3 L	
Aspiration	Natural, with dual element air cleaner		
Emissions System	EPA Tier 4, using combined DOC + DPF		
Fuel Capacity	9.3 gallons		
Main Clutch	Dry single disc, operated via left side foot pedal		
Speeds	12 forward x 12 reverse (4 gears, 3 ranges)		
Shuttle Type	Synchronized, with left hand shuttle lever		
Differential Lock	Mechanical, heel pedal		
Rear Brakes	Wet disc brakes with suspended R and L pedals		
Front Axle Type	4wd with mechanical engagement		
Rear PTO Type	Independent, electronically engaged		
Rear PTO Speed	540 and 540e rpm standard		
Implement Hydraulics	Open center system		
Hydraulic Flow at Remotes	8.9 gpm	11.1 gpm	
Loader Joystick	Standard with 2 mid mount valves		
Rear Remote Valves	0 standard, 2 optional	2 standard	
3-point Type	Category I with telescopic stabilizers and lower links		
3-point Lift Capacity	3,306 lbs at ball ends		
Operator's Area	Folding ROPS	Cab w/HVAC	
Seat and Steering	Adjustable vinyl seat; tilt steering		
Overall Length/Wheelbase	130 in / 70.9 in		
Height over ROPS/Cab	94 in	96 in	97 in
Base Weight	4,053 lbs	4,118 lbs	4,442 lbs

Loader Model	160C	180C
Max. Lift Height Under Bucket	92.5 in	101 in
Lift Capacity to Max. Height 19.5" Forward of Pivot	2,361 lbs	2,628 lbs
Breakout Force 19.5" Forward of Pivot	2,985 lbs	3,711 lbs
Rollback Force 31.5" Forward of Pivot	4,098 lbs	5,721 lbs
Compatible Tractor Models	X1.35	X1.45 X1.45C

